

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application. The current status of claims 1-42 is as follows:

1. – 21. (Cancelled).

22. (Currently Amended). A D-ring handle for use with emergency vehicles, said D-ring handle comprising:

(a) a D-shaped ring member having a curved leg and a base, said D-shaped ring member having a unitary construction, said leg and said base are integrally attached to one another;

(b) at least one tab integrally connected to said base, with said base of said D-shaped ring member rotatably coupled to a substrate member, such that pressure on said at least one tab moves said D-shaped ring member outward; and,

(c) a foot member including a pair of opposed supports for being hingedly attached to said D-shaped ring member, said foot member configured for rotatably coupling to a substrate member to actuate a latch member.

23. (Currently Amended). The D-ring handle of ~~Claim~~ claim 22, wherein said base includes a block member, integrally attached to said base, said block member includes a hole that passes through said block member, and said foot member includes said pair of opposed supports, which receive and hold a pin member, which passes through said block member and at least partially through each of said opposed supports to rotatably attach said D-shaped ring member to a substrate member.

24. (Currently Amended). The D-ring handle of ~~Claim~~ claim 22, wherein said base includes at least two tube members and said foot member includes said pair of opposed supports, which receive and hold a pin member, which passes through said tube members and at least partially through each of said opposed supports to rotatably attach said D-shaped ring member to a substrate member.

25. (Previously Presented). A D-ring handle for use with emergency vehicles, said D-ring handle comprising:

- (a) a D-shaped ring member configured for being hingedly coupled to a faceplate, said D-shaped ring member having a curved leg and a base, said D-shaped ring member having a unitary construction, said leg and base being integrally attached to one another;
- (b) at least one tab integrally connected to said base, said D-shaped ring member configured for being rotatably coupled to a faceplate, said at least one tab configured with respect to said base such that when pressure is applied thereto, said D-shaped ring member moves outward; and,
- (c) a foot member including a pair of opposed supports for receiving a portion of said base member, and configured for rotating relative to a faceplate for actuating a latch member.

26. – 35. (Cancelled).

36. (Previously Presented). The D-ring handle of claim 23, additionally comprising: a substrate member.

37. (Previously Presented). The D-ring handle of claim 24, additionally comprising: a substrate member.

38. (Previously Presented). The D-ring handle of claim 22, wherein said base includes a top edge and said at least one tab is connected to said base at said top edge.

39. (Previously Presented). The D-ring handle of claim 38, wherein said at least one tab includes one tab.

40. (Previously Presented). The D-ring handle of claim 25, wherein said base includes a top edge and said at least one tab is connected to said base at said top edge.

41. (Previously Presented). The D-ring handle of claim 40, wherein said at least one tab includes one tab.

42. (Previously Presented). The D-ring handle of claim 25, additionally comprising: a faceplate.